


Specification Sheet

Description **TRANSCUBE 20TCGCAB**

EPA Approved IBC (Intermediate Bulk Container) approved for the transport of diesel fuel.

The TRANSCUBE Global is fully bunded (steel in steel) to ensure environmental compliance with EPA Guidelines .



- ✿ 2000 litre model can be transported full of diesel without the need for ADR driver training.
- ✿ Featuring a large 700mm deep lockable cabinet to house all pumps and equipment
- ✿ Easily stacked 2 high full, 3 high empty to reduce storage space requirements.
- ✿ Access manhole for maintenance and inspection of inner tank.
- ✿ Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TRANSCUBE 20TCGCAB full of fuel.
- ✿ Secure lockable access hatch to house pumps (electric and hand!) and feed and return connections for up to 3 generators.
- ✿ Ability to supply fuel for up to 3 generators and refuel plant machinery all at the same time.
- ✿ Sized to stack inside shipping containers and across truck beds providing economical transportation.
- ✿ Protective galvanised framework preventing damage to tank, paintwork and decals.

Specifications

Standard Tank Fittings: 3" Fill Point : 2" Fill Point : Gauge : Pressure Vacuum Vent : Breather Vent : 1 x ¾" Pump Feed : 1 x ½" Generator Feed & Return : 4 x 1½" Sockets : 1 x ½" Socket : Inspection Manhole : Pump Bracket

Capacity (brim full) Litres:	2000	Weight Laden (kg):	2695
Capacity (brim full) Gallons:	440	Weight Unladen (kg):	895
Dimension Length (mm):	2300	Inner Tank Material (thickness):	3mm
Dimension Width (mm):	1550	Bund Material (thickness):	3mm
Dimension Height (mm):	1320	Design Approvals:	TAN 09066
Cabinet Dimensions (mm) Opening Size:	700mm	Design Standards:	UN Model Regulations, Chapter 6.5