

# Specification Sheet

Description **Fuelchief Container Tank FT30**



Fuelchief's range of double skinned diesel storage container tanks (known as the FT Series) has been designed to meet the most stringent environmental standards and to operate in the most severe conditions. Our Fuelchief self-bunded container tanks are designed to be durable and for situations where the tank will be subject to frequent relocation and where increased lifetime is of importance.

Below are the benefits and features of this tank:

- ♥ Self-contained, bunded (double wall) design with any spills contained in the unit
- ♥ Container corner castings for ease of transportation
- ♥ Permanent ladder and platform complete with kick-boards for ease of inspection and access – ladder can be fitted to either side
- ♥ Constructed using COR-TEN® (350mpa) steel to resist corrosion
- ♥ Water collection well complete with evacuation pipe
- ♥ Interstitial space integrity management system utilizing dipstick
- ♥ Containment compartment with pressure vent
- ♥ Lockable pump bay with spill containment and removable ventilation panels
- ♥ Free to air vent with weather cap
- ♥ Calibrated anodized fluid level dipstick
- ♥ Front mounted security doors with container lock handles
- ♥ White marine grade polyurethane paint
- ♥ Statutory signage

Ext Dimensions (l,w,h)	Capacity (total)	Capacity (SFL)	Weight (empty)
6058 x 2438 x 2896mm	30,000L	28,000L	8400kg
Design Standard	Inner Tank	Outer Tank	
AS1940, AS1692, AS1657	6mm	6mm	