

# Specification Sheet

Description **Fuelchief Container Tank FT68**



Fuelchief's range of double-skinned diesel storage container tanks (known as the FT Series) has been designed to meet the most stringent environmental standards and to operate in the most severe conditions. Below are some of the tank's key features:

- ♥ **Storage options:** diesel and waste oil only
- ♥ **Extra security:** thanks to enclosed pump cabinets
- ♥ **Prevention of fuel contamination:** due to improved inner tank design with a sloping floor for any water catchment within the tank
- ♥ **Eliminated risk of pollution:** a double-outer wall design is capable of holding 110% of the capacity of the inner tank (minimising leakage)
- ♥ **Spill containment:** due to double wall (self-bunded) design spills are contained in the unit
- ♥ **Meets legislation and certification:** built to Australian and New Zealand standards of AS/NZ 1692 and AS1940
- ♥ **Corrosion resistant:** constructed with corrosion-resistant steel (known as COR-TEN® (350mpa) steel)
- ♥ **Easy transportation of tank:** due to container corner castings
- ♥ **Water collection well:** complete with an evacuation pipe
- ♥ **Interstitial space:** (space between the inner and the outer tank) integrity management system utilizing dipstick
- ♥ **Containment compartment:** with pressure vent
- ♥ **Ventilation:** free to air vent with a weather cap (stops water entering the tank)
- ♥ **Measurement tool:** fuel level indicator dipstick provided
- ♥ **Security doors:** front mounted security doors with container lock handles
- ♥ **Durable paint:** white marine grade polyurethane paint
- ♥ **Easy access for maintenance and measuring:** permanent ladder and platform complete with kick-boards for ease of inspection and access – ladder can be fitted to either side
- ♥ **Required certified signage:** as indicated by customer/regulator
- ♥ **Warranty:** 3 years for tank and 1 year for internals

Ext Dimensions (l,w,h)	Capacity (total)	Capacity (SFL)	Weight (empty)
12192 x 2438 x 2896mm	65,000L	61,900L	15000kg
Design Standard	Inner Tank	Outer Tank	
AS1940, AS1692, AS1657	6mm	6mm	